


SCHMATIC



SPECIFICATION

- 1. Rating : DC 30V 0.5A
- 2. Contact resistance : $\leq 0.03\Omega$
- 3. Insulation resistance : $\geq 100M\Omega$ (DC250V)
- 4. Withstand voltage : 500VAC
- 5. Insertion and extraction force : 3-20N
- 6. life test : 5,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
6	HOUSING	1	PBT	
5	CONTACT	1	BRASS	Ag-Plating
4	FOOT	1	BRASS	Ni-Plating
3	FLAT PIECE	1	BRASS	Ag-Plating
2	CURVE PIECE	1	BRASS	Ag-Plating
1	SPRING	1	BRONZE	Ag-Plating

<small>UNLESS OTHERWISE SPECIFIED TOLERANCES ARE</small> .x ±0.30 .xx ±0.20 .xxx ±0.10 .x° ±3.0° .xx° ±2.0° .xxx° ±1.0°	UNIT: MM	TYPE:	MODEL NO:	PAGE 1 OF 1	
		DC JACK	DC00300-X	PAPER NO: A4	SCALE
	DESIGNER BY:	CHECK BY:	APPROVED BY:	3:1	
			承永實業有限公司 BLUE SOURCES ELECTRONICS CO.,LTD.		
				VER	1