


P.C.B LAYOUT
TOP VIEW

PIN	φ1.65	φ2.0	φ2.5
APPD	-AG	-AH	-AJ

- SPECIFICATION**
1. Rating : DC 20V 3.0A
 2. Contact resistance : $\leq 0.03\Omega$
 3. Insulation resistance : $\geq 100M\Omega$ (DC250V)
 4. Withstand voltage : 500VAC
 5. Insertion and extraction force : 3-20N
 6. Life test : 5,000 cycles



SCHEMATIC

7	HOUSING	1	PBT		
6	COAT	1	STAINLESS STEEL		Ni-Plating
5	CONTACT FOOT	1	BRASS		Ni-Plating
4	PIN	1	BRASS		Ni-Plating
3	CONTACT FOOT	1	BRASS		Ag-Plating
2	CURVE PIECE	1	BRASS		Ag-Plating
1	SPRING	1	BRONZE		Ag-Plating
NO.	DESCRIPTION	QTY	MATERIAL		PLATING

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

X	±0.30
.XX	±0.20
.XXX	±0.10
.X°	±30°
.XX°	±20°
.XXX°	±10°

UNIT: MM	TYPE: DC JACK	MODEL NO: DC0044A-XX-PBT
DESIGNER BY:		
CHECK BY:		
APPROVED BY:		

PAPER NO: A4	PAGE 1 OF 1
SCALE	VER
	1

丞永實業有限公司
BLUE SOURCES ELECTRONICS CO.,LTD.