



P.C.B. Layout
(Copper-sided view)

SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: $\leq 30m\Omega$;
3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-25N;
6. Life test: 5,000 cycles.

REV. LTR.	DESCRIPTION	SIGN	DATE

Model NO.	PJ2002M-C
Schematic	

: TERMINAL NO.

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
⑤	Shunt terminal	1	Brass	Sn-Plating
④	Tip spring	1	Phosphor bronze	Sn-Plating
③	Earth spring	1	Brass	Sn-Plating
②	Bushing	1	Copper alloy	Ni/Au/Cu-Sn-Plating
①	Housing	1	PBT	

UNIT:MM	TYPE:	MODEL NO:	PAPER NO: A4	PAGE 1 OF 1
	02.5 PHONE JACK	PJ2002M-C	TOLERANCE ANGLES	SCALE
DESIGNER BY:	Zhuhong	2008/11/24	±0.3	±2°
CHECK BY:			FULL	VER
APPROVED BY:				2

丞永實業有限公司
BLUE SOURCES ELECTRONICS CO.,LTD.