


SCHEMATIC



- SPECIFICATION**
1. Rating : DC 30V 0.5A
 2. Contact resistance : $\leq 0.03\Omega$
 3. Insulation resistance : $\geq 100M\Omega$ (DC250V)
 4. Withstand voltage : 500VAC
 5. Insertion and extraction force : 3-25N
 6. life test : 5,000 cycles

| NO. | DESCRIPTION | QTY | MATERIAL | PLATING |
|-----|--------------|-----|-----------|------------|
| 6 | COVER | 1 | PA66 /PBT | |
| 5 | HOUSING | 1 | PA66 /PBT | |
| 4 | AXIS SUPPORT | 1 | H59 BRASS | Ni-Plating |
| 3 | CURVE PIECE | 1 | H62 BRASS | Sn-Plating |
| 2 | SPRING PIECE | 1 | SUS301 | Sn-Plating |
| 1 | FLAT PIECE | 1 | H62 BRASS | Sn-Plating |

| | | | | | | |
|--|--|-------------------------------------|------------------|-------------------|--------------|-------------|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS | | UNIT: MM | TYPE: PHONE JACK | MODEL NO: PJ30160 | PAPER NO: A4 | PAGE 1 OF 1 |
| DESIGNER BY: | CHECK BY: | APPROVED BY: | TYPE: | MODEL NO: | PAPER NO: | PAGE 1 OF 1 |
| .x ±0.30 .xx ±0.20 .xxx ±0.10 | .x* ±3.0* .xx* ±2.0* .xxx* ±1.0* | .x ±0.30 .xx ±0.20 .xxx ±0.10 | TYPE: | MODEL NO: | PAPER NO: | PAGE 1 OF 1 |
| 丞永實業有限公司 BLUE SOURCES ELECTRONICS CO.,LTD. | | | | | | |