



P.C.B LAYOUT
TOP VIEW

SCHMATIC

PJ3017H	PJ3017H-1	PJ3017H-2	PJ3017H-3	PJ3017H-5

- SPECIFICATION
1. Rating : DC 30V 0.5A
 2. Contact resistance : $\leq 0.03\Omega$
 3. Insulation resistance : $\geq 100M\Omega$ (DC250V)
 4. Withstand voltage : 500VAC
 5. Insertion and extraction force : 3-20N
 6. life test : 5,000 cycles

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
.X	± 0.30
.XX	± 0.20
.XXX	± 0.10
.X°	$\pm 3.0^\circ$
.XX°	$\pm 2.0^\circ$
.XXX°	$\pm 1.0^\circ$

UNIT: MM	TYPE:	MODEL NO:	PAPER NO: A4	PAGE 1 OF 1
	PHONE JACK	PJ3017H-X		SCALE 3:1
NO.	DESCRIPTION	QTY	MATERIAL	PLATING
8	SPRING	1	SUSS301 T=0.2	Ni-Plating
7	COVER	1	PBT	
6	HOUSING	1	PBT	
5	5# CONTACT FOOT 1		BRONZE	Sn-Plating
4	4# CONTACT FOOT 1		H62 BRASS	Sn-Plating
3	3# CONTACT FOOT 1		H62 BRASS	Sn-Plating
2	2# CONTACT FOOT 1		BRONZE	Sn-Plating
1	1# CONTACT FOOT 1		BRASS	Sn-Plating

DESIGNER BY:	CHECK BY:	APPROVED BY:	<p>承永實業有限公司</p> <p>BLUE SOURCES ELECTRONICS CO.,LTD.</p>