


P.C.B LAYOUT
TOP VIEW

SCHMATIC



- SPECIFICATION
1. Rating : DC 30V 0.5A
 2. Contact resistance : $\leq 0.03\Omega$
 3. Insulation resistance : $\geq 100M\Omega$ (DC250V)
 4. Withstand voltage : 500VAC
 5. Insertion and extraction force : 3-20N
 6. life test : 5,000 cycles

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
.XX	± 0.30
.XXX	± 0.20
.XXX*	± 0.10
.X°	$\pm 3.0^\circ$
.XX°	$\pm 2.0^\circ$
.XXX°	$\pm 1.0^\circ$

UNIT: MM	TYPE:	MODEL NO:	PAPER NO: A4	PAGE 1 OF 1
	PHONE JACK	PJ30180-X		SCALE 3:1
DESIGNER BY:				VER 1
CHECK BY:				
APPROVED BY:				
NO.	DESCRIPTION	QTY	MATERIAL	PLATING
5	SPRING PIECE	1	PHOSPHOR BRONZE	Ag-Plating
4	CURVE PIECE	1	H62 BRASS	Ag-Plating
3	FLAT PIECE	1	H62 BRASS	Ag-Plating
2	AXIS SUPPORT	1	H59 BRASS	Ni-Plating
1	HOUSING	1	PAG6	

承永實業有限公司
BLUE SOURCES ELECTRONICS CO.,LTD.