



SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: $\leq 30m\Omega$;
3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-30N;
6. life test: 5,000 cycles.

Model NO.	PJ301CM-D
Schematic	

: TERMINAL NO.

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
①	Housing	1	PBT	
②	Bushing	1	Brass	Ni/Cu-Sn-Plating
③	Earth spring	1	Bronze	Sn-Plating
④	Tip spring	1	Brass	Sn-Plating
⑤	Ring spring	1	Stainless Steel	Sn-Plating
⑥	Nut	1	Brass	Ni-Plating

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
x	±0.30
xxx	±0.20
xxxx	±0.10
x°	±30°
xx°	±20°
xxx°	±10°

DESIGNER BY:	Zhuhong 2008/10/16	MODEL NO:	PJ301CM-D	PAPER NO:	A4	PAGE 1 OF 1
CHECK BY:						SCALE
APPROVED BY:						FULL
						VER
						1

丞永實業有限公司
BLUE SOURCES ELECTRONICS CO.,LTD.

REV. LTR	DESCRIPTION	SION	DATE
A	如標示共五項	王旭梅	2010.07.07.