


P.C.B LAYOUT
TOP VIEW

SCHEMATIC



- SPECIFICATION**
1. Rating : DC 30V 0.5A
 2. Contact resistance : $\leq 0.03\Omega$
 3. Insulation resistance : $\geq 100M\Omega$ (DC250V)
 4. Withstand voltage : 500VAC
 5. Insertion and extraction force : 3-20N
 6. Life test : 5,000 cycles

5	HOUSING	1	PBT				
4	3#SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating			
3	CONTACT FOOT	1	BRASS	Sn-Plating			
2	2#SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating			
1	1#SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating			
NO.	DESCRIPTION	QTY	MATERIAL	PLATING			
UNIT: MM		MODEL NO:		PAGE 1 OF 1			
TYPE: PHONE JACK		PJ30220-X		SCALE 4:1		VER 1	
DESIGNER BY:		PAPER NO: A4					
CHECK BY:							
APPROVED BY:							
<p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS</p> <p>° ±3.0° x° ±2.0° xxx° ±1.0°</p> <p>x ±0.30 xx ±0.20 xxx ±0.10</p>							