

- NOTES:
1. CONTACT CURRENT RATING: 1A.
  2. CONTACT RESISTANCE: 50 mΩ MAX.;
  3. INSULATION RESISTANCE: 100MΩ MIN.;
  4. DIELECTRIC WITHSTANDING: 500V AC MIN.;
  5. DURABILITY: 5,000 CYCLES MIN.;
  6. CONNECTOR MATING FORCES: 29.4N (3.00kgf) MAX.;
  7. CONNECTOR UNMATING FORCES: 2.94N(0.30kgf) MIN.;
  8. PRODUCT MEET THE REQUEST OF THE RoHs, SEE TABLE A:

ITEM	PART NAME	Q'TY	MATERIAL	DESCRIPTION	REMARK
⑦	HOUSING	1	LCP		Black
⑥	CONTACT F	1	PHOSPHOR BRONZE 0.20T	Au PLATED	
⑤	CONTACT E	1	BRASS 0.20T	Au PLATED	
④	CONTACT D	1	PHOSPHOR BRONZE 0.20T	Au PLATED	
③	CONTACT C	1	PHOSPHOR BRONZE 0.20T	Au PLATED	
②	CONTACT B	1	PHOSPHOR BRONZE 0.20T	Au PLATED	
①	CONTACT A	1	PHOSPHOR BRONZE 0.20T	Au PLATED	

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:

.XX	±0.30
.XX	±0.20
.XXX	±0.10
.X°	±3.0°
.XX°	±2.0°
.XXX°	±1.0°

UNIT: MM

DESIGNER BY:

CHECK BY:

APPROVED BY:


TYPE: PHONE JACK CUSTOMER DRAWING

MODEL NO: PJ3105C-X

PAPER NO: A4

PAGE 1 OF 1  
SCALE 3:1  
VER 1

SCHEMATIC



承永實業有限公司  
BLUE SOURCES ELECTRONICS CO.,LTD.